WO 2005/046422 PCT/EP2004/012244

- 11 -

CLAIMS

15

25

- 1. A device for cleaning a substrate such as a fabric comprising:
- 5 (a) A reservoir for storing a fabric cleaning fluid,
 - (b) a scrubbing member for scrubbing the fabric, the scrubbing member in fluid communication with the reservoir,
- (c) the scrubbing member comprising one or more dispensing orifices,
 - (d) a movable platform for forcing said cleaning fluid to exit from the reservoir to the scubber member, where it is exposed on an exterior portion of the scrubber member via said dispensing orifices, for cleaning purposes.
 - 2. A device according to claim 1 wherein the platform comprises a wall or base portion of the reservoir and sliding the platform within the reservoir,
- progressively compresses the cleaning composition which is thereby forced to exit the reservoir and flow to the scrubbing means.
 - 3. A device according to any preceding claim in which the reservoir is in fluid communication with the scrubbing means by way of an exit orifice or orifices.
 - 4. A device according to any preceding claim in which the reservoir is refillable with cleaning fluid or components thereof, by a user.
- 5. A device according to any preceding claim in which the reservoir has a removable portion e.g. end cap and optionally scrubbing means for refilling purposes.

WO 2005/046422 PCT/EP2004/012244

- 12 -

- 6. A device according to any preceding claim in which the dispensing orifices are provided by a mesh fabric.
- 7. A device according to any preceding claim in which the platform is configured for reciprocal generally axial movement within a generally tubular reservoir.

5

10

15

- 8. A device according to any preceding claim in which the platform is movable by means of screw feed mechanism.
- 9. A device according to any preceding claim in which the platform has a peripheral edge configured to slide in a sealing relationship with an inner surface of the reservoir, whereby sliding is guided by said inner surface.
 - 10. A method of cleaning a fabric using the device according to any preceding claim, the method comprising the steps of:
 - (a) filling the reservoir with a cleaning fluid, optionally optained by mixing a solid cleaning composition e.g. powder, granules, and a solvent e.g. water to form a cleaning fluid within the reservoir,
- 20 (b) securing a removable portion e.g. end cap and scrubbing member on the device to close the reservoir,
 - (c) moving the platform e.g by turning a screw-feed mechanism to force cleaning fluid from the reservoir to be exposed on the exterior of the scrubbing means; and
- 25 (d) cleaning the fabric by scrubbing with said scubbing means.